



### Main

For Artec, Tracent, Antique.

With integrated bus coupling unit.

Push-button with eight operating buttons, operating display, eight blue status displays which can be triggered separately, and a labelling field. The blue operating display can also be used as an orientation sign. The lower labelling field can be parameterised as an additional operating key.

The push-buttons are freely parameterisable as push-button pairs (dual-surface) or as single push-buttons.

### Complementary

The device is connected to the bus line with a bus connecting terminal.

#### KNX software functions:

Switching, toggling, dimming (single/dual-surface), blind (single/dual-surface), pulse edges trigger 1-, 2-, 4- or 8-bit telegrams (distinction between short and long operation), pulse edges with 2-byte telegrams (distinction between short and long operation), 8-bit linear regulator, scene retrieval, scene saving, disable functions.

**Accessories:** Labelling sheets for push-button plus art. no. MTN617819.

Contents: With protective hood for plaster. With bus connecting terminal.

Material : Thermoplastic brilliant

Colour: aluminium

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.